

System cable / Systemkabel: M23 / RC16-7p. HT

Pin am Systemstecker / Pin on system socket	Farbkennzeichnung / Colour identification (Farbadern / colored cores)	Nummerierung / Numbering (aufgedruckt / imprinted)	Systemname / System name
6	brown / braun	1	OUT0-
7	red / rot	2	OUT0+
8	orange / orange	3	OUT1-
9	yellow / gelb	4	OUT1+
10	bridge / Brücke zu pin14		IN0-
11	green / grün	5	IN0+
14	blue / blau	6	U-
15	purple / violett /	without / ohne	U+

Order No. / Bestellnummer	Cable type / Kabeltyp	Temperature range / Temperaturbereich	Comments / Bemerkungen
2301A120xmHT	ÖLFLEX HEAT 125 C MC 7G 1 straight / gerade	stationary / stationär: (-55 ... 125) °C moving / bewegt: (-35 ... 120) °C	halogen free / halogenfrei
2301A190xmHTA	ÖLFLEX HEAT 125 C MC 7G 1 angled / gewinkelt	stationary / stationär: (-55 ... 125) °C moving / bewegt: (-35 ... 120) °C	halogen free / halogenfrei

xm ... Length [m] / Länge [m]

xm = [5, 10, 15, 20, 30]; others on request / andere auf Anfrage

