

Ethernet cable / Ethernetkabel: M12A– RJ45 cross / patch (HT)


Pin RJ45	Colour identification / Farbkennzeichnung	Cross cable Pin M12A	Patch cable Pin M12A	System name / Systemname
1	orange-white / orange-weiß	5	6	D1+
2	orange / orange	8	4	D1-
3	green-white / grün-weiß	6	5	D2+
4	blue / blau	2	7	D3+
5	blue-white / blau-weiß	3	1	D3-
6	green / grün	4	8	D2-
7	brown-white / braun-weiß	7	2	D4+
8	brown / braun	1	3	D4-

TIA/EIA-568B


Order No. / Bestellnummer	Type	Cable type / Kabeltyp	Temperature range / Temperaturbereich	Comments / Bemerkungen
2301A320xm	cross	CAT.5e 4 x 2 x 26AWG straight / gerade	stationary / stationär: (-30 ... 80) °C rare motion / wenig bewegt: (-5 ... 50) °C	polyurethane / Polyurethan halogen free / halogenfrei flame-retardant / schwer entflammbar
2301A330xm	patch			
2301A320xmHT	cross	CAT.5e 4 x 2 x 26AWG straight / gerade	stationary / stationär: (-40 ... 125) °C	TPE
2301A320xmHTA	cross	CAT.5e 4 x 2 x 23AWG angled / gewinkelt		

xm ... Length [m] / Länge [m]

xm = [5, 10, 20, 25, 30, 50], others on request / andere auf Anfrage



M12A



RJ45