

System cable / Systemkabel: M23 / RC16-16p.

Pin on system socket / Pin am Systemstecker	Colour identification / Farbkennzeichnung	System name / Systemname
1	white / weiß	
2	brown / braun	
3	green-yellow / grün-gelb	
4	green / grün	
5	yellow / gelb	
6	gray / grau	OUT0-
7	pink / rosa	OUT0+
8	blue / blau	OUT1-
9	red rot	OUT1+
10	black / schwarz	IN0-
11	purple / violet	IN0+
12	gray-pink / grau-rosa	IN1-
13	red-blue / rot-blau	IN1+
14	brown (blue marker) / braun (Markierung blau)	U-
15	white (red marker) / weiß (Markierung rot)	U+
16		n.c.

n.c. ... not connected / nicht angeschlossen

Order No. / Bestellnummer	Cable type / Kabeltyp	Temperature range / Temperaturbereich	Comments / Bemerkungen
2301A120xm	ÖLFLEX FD 770 CP 6x2x0,25+2x0,50 open ends / offenen Enden	stationary / stationär: (-50 ... 80) °C moving / bewegt: (-40 ... 80) °C	high flexible / hoch flexibel halogen free / halogenfrei
2301A190xm	ÖLFLEX FD 798 CP 6x2x0,25+2x0,50 open ends / offene Enden	stationary / stationär: (-50 ... 80) °C moving / bewegt: (-40 ... 80) °C	high flexible / hoch flexibel halogen free / halogenfrei IP 67 / IP 69K (EN 60529) ATEX

xm ... Length [m] / Länge [m]

xm = [5, 10, 15, 20, 25, 30]; others on request / andere auf Anfrage

